

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
14 July 2005 (14.07.2005)


PCT

(10) International Publication Number  
**WO 2005/064827 A1**

- (51) International Patent Classification<sup>7</sup>: **H04B 10/08** (74) Agent: MAGNUSSON, Monica; Ericsson AB, Patent Unit Radio Networks, S-164 80 Stockholm (SE).
- (21) International Application Number: PCT/SE2004/002042 (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 28 December 2004 (28.12.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/532628 29 December 2003 (29.12.2003) US
- (71) Applicant (for all designated States except US): TELEFONAKTIEBOLAGET LM ERICSSON (PUBL). [SE/SE]; S- 164 83 Stockholm (SE).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): KALLSTENIUS, Thomas [SE/SE]; 31, rue N.S. Pierret, L-2335 Luxembourg (LU).
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: TEMPERATURE COMPENSATION FOR TRANSMISSION BETWEEN NODES COUPLED BY A UNIDIRECTIONAL FIBER RING



(57) Abstract: Transmissions over a unidirectional optical fiber coupling multiple nodes are compensated for temperature-induced effects. A round-trip delay time is determined for a signal sent from a first node to travel around the unidirectional optical fiber loop and be received back at the first node. That measured round-trip delay time is then used to account for temperature-induced effects on signal transmissions over the unidirectional optical fiber loop. This temperature compensation is particularly beneficial in applications that require a high level of timing accuracy.

WO 2005/064827 A1



**Declaration under Rule 4.17:**

— of inventorship (Rule 4.17(iv)) for US only

**Published:**

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*